

Flat Ribbon Fibre Optic Patch Cable (4-12 Fibres)

Optronics flat ribbon fibre optic patch cable is constructed with 4 - 12 ribbonised optical fibres protected by soft aramid yarns and an LSZH jacket. Ideal for use in office LAN connections, patchcords and internal point-to-point links where frequent handling is likely (e.g. data cabinets, equipment rooms, user outlets).

Features/Benefits

- > Choice of fibre type
- > Choice of outer diameter
- > High strength aramid yarn strength members for ease of handling
- > Easy to strip
- > LSZH jacket

Applications

- > Patchcords
- > Pigtails
- > Internal inter-connections

Technical Specifications

DESCRIPTION		4-CORE LSZH	6-CORE LSZH	8-CORE LSZH	12-CORE LSZH
Outer Diameter	mm	3.5*2.5	3.8*2.5	4.5*2.5	5.0*2.5
Weight	kg/km	14	15	17	19
Max. Load (installation)	N	200	200	200	200
Max. Load (installed)	N	80	80	80	80
Min. Bend Radius (installation)	Times	35	35	35	35
Min. Bend Radius (installed)	Times	25	25	25	25
Fire Performance		LSZH	LSZH	LSZH	LSZH
Operating Temp.	°C	-20~+60	-20~+60	-20~+60	-20~+60
Storage Temp.	°C	-20~+70	-20~+70	-20~+70	-20~+70
Installation Temp.	°C	-20~+60	-20~+60	-20~+60	-20~+60
Crush Resistance	N/100mm	500	500	500	500

Ordering Information

PRODUCT DESCRIPTION	PART NO.
OM1	OM1RIBBONOR**-C/Z
OM2	OM2RIBBONOR**-C/Z
OM3	OM3RIBBONAQ**-C/Z
OM4	OM4RIBBONAQ**-C/Z
OS1/OS2	OS1RIBBONYE**-C/Z

Where ** is the fibre count between 4 & 12



Fire Retardant Internal Use Standard Length

